



# ROLL UP DOOR SPEC SHEET

AVAILABLE ANYWHERE IN  
THE CONTINENTAL US

**DON'T WAIT,  
CALL TODAY!  
(865) 316-9009**

## **Roll-Up Door Spec Sheet:**

### **Curtain:**

26 Gauge Galvanized Steel  
Polyester WeatherXL Paint  
Maximum Door Opening: up to 10'x10'  
Standard Mini Latch Factory Installed, Cylinder Latches Field Installed  
Felt Strips down length of curtain allows quieter, smooth operation and reduces surface abrasion

### **Bottom Bar:**

.075 Thick Aluminum Extrusion  
6063-T6 Aluminum Extrusion  
1.5" x 1.5" 14 Gauge Angle  
1.125" Tall Astragal Weather Strip  
.100" Thick Astragal Weather Strip

### **Axle Assembly:**

1 5/16" O.D. Steel Axle, 14 Gauge  
Oil Tempered, E-Coated Torsion Springs  
9.5" Diameter Drums, 18 Gauge Galvanized Steel  
Live Axle Assembly

### **Tension Bracket, Guide Rails and Hardware:**

High Quality Steel Bearings for long-lasting, easy operation of door  
18 Gauge Steel Guide Rails with plastic wear strip for curtain protection  
Steel Head Stop and Catch to secure door inside guide rails



**(865) 316-9009**  
[info@roimetalbuildings.com](mailto:info@roimetalbuildings.com)



**6800 Waller Ferry Rd.  
Suite B,  
Lenoir City, TN 37771**